

## SERIE 67/8- KEYCOMBI

LA COMBINAZIONE BLOCCA LA CHIAVE  
THE KEY MECHANISM CAN BE BLOCKED BY THE COMBINATION LOCK



### COSTRUZIONE RINFORZATA

Porta acciaio 8 mm, spessore totale 55 mm, tagliata laser. Apertura a tutta luce, cerniera a tutta altezza. Battute a U spessore 4 mm antisfondamento. Catenacci Ø 25 cromati, indipendenti, girevoli, montati su doppio supporto 4+4 mm. Serrature corazzate con piastra di rinforzo in acciaio al manganese. Robuste saldature robotizzate. Coperchio interno imbutito, smontabile solo a serratura aperta. Corpo a pareti singole 5 mm. Fori Ø12 di fissaggio al dorso e alla base.

### CONGEGNO di CHIUSURA

Serratura a 8 leve effettive antimanipolazione, 2 mandate. Chiavi bicifrate (48.017.788 variazioni effettive) **Congegno Certificato a Norma Europea EN 1300 Classe B.**

### CONGEGNO di BLOCCO

Serratura a combinazione a 3 dischi coassiali, antimanipolazione. 3 Numeri, 1.440.000 variazioni possibili, cambio a chiave. Possibilità di azzeramento a porta aperta. **Congegno Certificato a Norma Europea EN 1300 Classe B.**

### REINFORCED CONSTRUCTION

Laser-cut steel door, 8 mm (total thickness 55mm) Full-light opening, full-height hinge. U-shaped, anti-smashing rabbets (4 mm). Chromium-plated, independent, turning bolts, Ø25 mm, mounted on double support 4+4 mm. Armoured locks protected by a reinforcement-plate in manganese-steel material. Strong robotized weldings. Internal deep-drawn cover, it can be dismantled just when lock is open. 5 mm single-wall body. Fixing holes (Ø 12 mm) at rear and base.

### CLOSING SYSTEM

Antimanipulation lock, 8 effective levers, 2 turns. Bicyphered keys (48.017.788 effective variations). **Device certified according to European Norm EN 1300 Class B.**

### BLOCKING SYSTEM

3-coaxial- wheels combination lock, antimanipulation. 3 Numbers; 1.440.000 possible variations; change by key. The combination can be set at zero if door is open. **Devis certified according to the European Norm EN 1300 Class B.**

67/8	DIMENSIONI mm							LUCE PORTA DOOR OPENING		CATENACCI BOLTS	RIPIANI SHELVES	PESO WEIGHT Kg
	art.	N.	H/H	L/W	P/D	H/H	L/W	P/D	H/H			
6738	3A	305	375	290	295	365	226	216	272	2+2	1	35,8
6778	6V	610	410	380	600	400	316	436	272	3+2	1	67,2